

Highlights:

- Stores up to 42 units of 19" Equipment
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 740 mm)
- Tempered glass door with keylock
- Reversible door position
- Swing handle with cylinder lock
- Width of 800 mm for convenient installation and maintenance
- Available space on sides for cable management systems and accessories

The SPR8842 is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provide a solid and stable construction making it suitable for heavy equipment, storing up to 42 units inside. The SPR8842 comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and levelling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19 " profiles provide great flexibility for installing equipment depending on its depth.

The SPR8842 comes with a tempered glass front door and steel rear door. The swing handle with cylinder lock safely locks the equipment inside. The width of 800 mm offers additional space for the installation of accessories and cable management systems, while guaranteeing an optimal convenience for installation and maintenance of the equipment.



Product Features:

Unit height		42 HE
Dimensions		800 x 1985 (2055) x 800 mm (W x H (incl. feet) x D)
Max. usable depth		740 mm
Wheel	Diameter	50 mm
Colours		Black (RAL9004)
Static load capacity (adjustable feet)		800 kg
Dynamic load capacity (transport castors)		400 kg
Weight		120 kg
Accessories	Included	4 x Key for sidepanel lock
		1 x Allen key
		1 x Levelling feet
		4 x Key for front/back door
		20 x KM600
		20 x KS600
	Optional	KS600 - M6 x 16 mm bolt DIN7985 Black
		SPR10CS - Rack interconnection slot
		KM600 - M6 Cage nuts
		SPR80LR - L-Rail pair
		SPR80FS - Fixed shelf
		SPR80SS - Sliding shelf
		SPR80RF - Cooling roof fan unit (230V)

Variants:

- SPR8842/B - Black version - 800mm width

