

BASSO118

18" ultra-high power infra-subwoofer

Highlights:

- 3000 Watt program power
- Low frequency extension down to 23Hz without processing
- 128 dB of Max SPL (continuous)
- Indoor model with Polyurea coated 18/36mm multiply plywood
- Weather resistant with marine grade plywood and Dura-Polyurea coating
- Extremely ridged chassis and inner framing

Product information:

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion.

Applications:

- Bars & Restaurants
- Hotels
- Clubs
- Sporting facilities
- Events
- Concert venues
- Museums & Themeparks



Properties:

 Weatherproof

Impedance:

Ω 8 Ohm

Usage:

 Indoor  Outdoor

System specifications:

Speaker type		18" Infra-Sub
Configuration		AeroVent
Peak power handling		6000 W
Program power handling		3000 W
Continuous power (AES)		1500 W
Impedance		8 Ω
Max SPL (Continuous)		131 dB
Sensitivity (1W/1m)		99 dB
Frequency	Response (- 3 dB)	30 Hz - 120 Hz
	Range (-10 dB)	23 Hz - 200 Hz
Bass port tuning frequency		33 Hz
Connectors		Terminal block with linkthrough
Drivers		18" carbon cone with dual suspension (low-loss) and 4" high excursion voice coil
Ingress Protection rating		IP55 (BASSO118/OB)

Product Features:

Dimensions		758 x 550 x 798 mm (W x H x D) (excluding feet)
		758 x 555 x 798 mm (W x H x D) (including feet)
Weight		45 kg
Operating temperature		-20 °C ~ 70 °C
Construction		18 mm Multiply Plywood with multi-layer Polyurea coating
Front finish		2.5 mm Steel grill with hexagon perforations and acoustic foam backing
Mounting & handling	Rigging points	12 x M10 mounting bracket installation holes on both sides
	Stand fitting	1 x M20 internal thread stand adapter
Colours		Black

Variants:

- BASSO118/B - Black version
- BASSO118/OB - Outdoor black version

Shipping & Ordering:

Packaging	Cardboard box
Shipping weight & volume	50 kg - 0.46 Cbm